

Preventative Maintenance Checklist

GS3 1 Year

Please fill out all sections completely			
Customer Name:	Service Provider:		
Phone:	Technician:		
Address:	Other Parts Used:		
	Mileage:		
Serial Number:	J		
All Models			
☐ Clean and Back Flush Machine			
Replace Group Gaskets	□ 8 mm (H.3.001)		☐ 9 mm (L105/B9)
☐ Replace Diffuser Screens (F.3.040)	Dealer Torre		
□ Replace Portafilter Baskets□ Inspect Group Valve Operation	Basket Type:		
☐ Test All Switches for Proper Operation	•	☐ Acceptable☐ Acceptable	
☐ Test Flow Rate	Group 1:	•	
☐ Test Brew Temperature Setting	Desired:		Current:
☐ Test Brew Pressure Setting			
☐ Clean Auto Fill Probe			
☐ Replace Steam Boiler Vacuum Breaker Valve (L193)			
☐ Test Auto Fill Valve for Proper Operation	☐ Replaced	☐ Acceptable	
☐ Replace Pressure Safety Valve (B.2.025)			
☐ Inspect Drain System			
☐ Test Water with La Marzocco Water Test Kit (F.9.000)			
If AV Model			
☐ Test Shot Volumes			
☐ Test Flow Meters for Correct Resistance	Group 1:	_	
If MP Model			
☐ Rebuild MP Valve (SA/600K)— only required on older m	nodels of the GS3 N	/IP New GS3 MPs w	vith a conical valve do not need to be rebuilt
this frequently. Contact @christopher@lamarzocco.com			The solution value as her need to be result.
Notes:			
Technician (Please Print):			
Technician Signature:			